

TYRES

Product group	Tyres	
Item number	10002900	
Valid tyre size	8.25 R 15	
LI / SI / PR	143 / 141 G (141 / 140 K), 18 PR	
TL/TT	тт	
Brand	Continental	
Tread pattern	Regional Traffic HTR+	





Technical Informations

Item number	10002900		
EAN	4019238042955		
Valid tyre size	8.25 R 15		
LI / SI / PR	143 / 141 G (141 / 140 K), 18 PR		
TL/TT	π		
Brand	Continental		
Tread pattern	Regional Traffic HTR+		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	TR		
Rolling resistance	D		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Wet grip	С
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	28,00
Recommended rim size	6.503
Maximum air pressure [bar].	8,50
Section width (mm)	234
Outer diameter of tyre [mm].	838
Stat. radius (SLR) [mm]	383
Rolling circumference [mm].	2568
Tread depth (mm)	13,2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 G	2725	90	Single	8,50	
141 K	2575	110	Single	8,50	
141 G	2575	90	Twin	8,50	
140 K	2500	110	Twin	8,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.