

## **TYRES**

Product group	Tyres	
Item number	10002918	
Valid tyre size	VF 600 / 70 R 30	
LI / SI / PR	168 D / 165 E	
TL/TT	TL	
Brand	Nokian	
Tread pattern	Soil King VF	



## **Technical Informations**

Item number	10002918
EAN	6419440486901
Valid tyre size	VF 600 / 70 R 30
LI / SI / PR	168 D / 165 E
TL/TT	TL
Brand	Nokian
Tread pattern	Soil King VF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	208,38
Recommended rim size	DW21B

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Permitted rim size	DW18L, DW20B
Maximum air pressure [bar].	2,80
Section width (mm)	615
Outer diameter of tyre [mm].	1598
Stat. radius (SLR) [mm]	697
Dynamic radius [mm]	767
Rolling circumference [mm].	4817
Tread depth (mm)	55,0
Tyre capacity 75% [ltr.]	465
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		2,80	
165 E	5150	70		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.