

## TYRES

Product group	Tyres
Item number	10002935
Valid tyre size	VF 1050 / 50 R 32 CFO
LI / SI / PR	198 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 377 +



## Notes and features

- The Alliance Agriflex 377+ is a VF tyre for manure spreaders, sprayers, harvesting vehicles and grain carts.
- The new tread ensures a maximum contact area for low soil compaction and optimum traction.
- The rounded tyre shoulder protects the ground and prevents tyre damage caused by stubble.
- VF technology enables up to 40% higher load capacity at the same air pressure compared to standard tyres.
- The steel belted carcass and a strong wear-resistant rubber compound ensure stability and durability.
- The robust rubber compound effectively protects the tyre from damage (Stubble Guard) and ensures a long service life.

**Technical Informations**

<b>Item number</b>	10002935
<b>EAN</b>	7291050085243
<b>Valid tyre size</b>	VF 1050 / 50 R 32 CFO
<b>LI / SI / PR</b>	198 D
<b>TL/TT</b>	TL
<b>Brand</b>	Alliance
<b>Tread pattern</b>	Agriflex 377 +
<b>Carcass properties</b>	Steel Belted
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	ECE 106
<b>Nettogewicht [kg] (gültig)</b>	424,00
<b>Recommended rim size</b>	36VA
<b>Maximum air pressure [bar].</b>	3,60
<b>Section width (mm)</b>	1059
<b>Outer diameter of tyre [mm].</b>	1863
<b>Stat. radius (SLR) [mm]</b>	821
<b>Speed Radius Index (SRI)</b>	675
<b>Rolling circumference [mm].</b>	5650
<b>Contact area [cm<sup>2</sup>]</b>	5622
<b>Tread depth (mm)</b>	46,0
<b>Number of lugs</b>	20x2
<b>Tyre capacity 75% [ltr.]</b>	1248.75
<b>Guarantee period</b>	10 years
<b>E-Ready</b>	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
198 D	13200	65		3,60	