

TYRES

Product group	Tyres
Item number	10002935
Valid tyre size	VF 1050 / 50 R 32 CFO
LI / SI / PR	198 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 377 +



Notes and features

- The Alliance Agriflex 377+ is a VF tyre for manure spreaders, sprayers, harvesting vehicles and grain carts.
- The new tread ensures a maximum contact area for low soil compaction and optimum traction.
- The rounded tyre shoulder protects the ground and prevents tyre damage caused by stubble.
- VF technology enables up to 40% higher load capacity at the same air pressure compared to standard tyres.
- The steel belted carcass and a strong wear-resistant rubber compound ensure stability and durability.
- The robust rubber compound effectively protects the tyre from damage (Stubble Guard) and ensures a long service life.

Technical Informations

Item number	10002935
EAN	7291050085243
Valid tyre size	VF 1050 / 50 R 32 CFO
LI / SI / PR	198 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 377 +
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	424,00
Recommended rim size	36VA
Maximum air pressure [bar].	3,60
Section width (mm)	1059
Outer diameter of tyre [mm].	1863
Stat. radius (SLR) [mm]	821
Speed Radius Index (SRI)	675
Rolling circumference [mm].	5650
Contact area [cm ²]	5622
Tread depth (mm)	46,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	1248.75
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
198 D	13200	65		3,60	