

TYRES

Product group	Tyres
Item number	10002936
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K, 24 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STM1



Bohnenkamp
Moving Professionals

 **SAILUN**
TYRE

Notes and features

- The Sailun STM1 is an all-position tyre, preferably used as drive tyre for vehicles in regional traffic.
- The special tread pattern design provides driving stability, excellent self-cleaning and good grip in all weather conditions.
- Its robust tyre shoulder as well as the reinforced bead construction guarantee a long service life.
- Protrusions in the tread grooves ensure particularly slow wear and protect against scratch damages.
- Due to the sturdy tread compound, the tyre is extremely puncture resistant.

Technical Informations

Item number	10002936
EAN	8935341205048
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K, 24 PR
TL/TT	TL
Brand	Sailun
Tread pattern	STM1
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR/RA/FA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	80,00
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	385
Tread width (mm)	310
Outer diameter of tyre [mm].	1072
Stat. radius (SLR) [mm]	496
Rolling circumference [mm].	3248

Tread depth (mm)	17,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 K	5000	110	Single	9,00	