

WHEELS

Product group	Wheels
Item number	10002938
Valid wheel size	16.00 - 25
Brand	BKT
Tread pattern	XL Grip
Valid rim size	11.25 - 25 / 2.0
Rim connection	24/371/425
Bolt hole design	M20
Offset (mm)	+85
Rim colour	Black
Load capacity complete wheel [kg]	7300
Speed complete wheel [km/h]	50



Technical Informations

Assembly Item no. Tyres	• 15772633
LI / SI / PR	32 PR
TRA Code	E3 L3
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	402,18
ECE regulation number	not necessary
Section width (mm)	465
Stat. radius (SLR) [mm]	682
Rolling circumference [mm].	4395
Tread depth (mm)	30,0

E-Ready	No
Assembly Item no. Rim	• 10002801
Load capacity of rim 1 [kg]	16900
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	15300
Speed Rims 2 [km/h]	30
Maximum speed [km/h].	50
Maximum air pressure [bar].	8,75
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	five-part
Rim material	steel
RAL	RAL9005
Colour type	Glossy
Cavity Sealed	No
Rim flange height [inch]	2.0
Disc thickness [mm]	18
Knurling	with knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	24
Bolt hole design EUWA	M20
Bolt hole diameter [mm]	24.0
hub hole diameter [mm].	371
Bolt hole circle diameter [mm]	425

Valve seat	External Valve
Valve hole diameter [mm]	20.5
Preassembled valve	No
Valve length [mm]	63.5
Valve angle [°]	103