

TYRES

Product group	Tyres
Item number	10002941
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K
TL/TT	TL
Brand	Continental
Tread pattern	Conti Hybrid HT3+



Notes and features

- The Continental Hybrid HT3+ is a truck trailer tyre for mixed use in regional, local and long-distance traffic.
- Its tread pattern with 4 circumferential grooves and improved pocket sipes guarantees perfect grip.
- It is suitable for all weather conditions, including winter road conditions.
- The special rubber compound ensures low heat generation and lower fuel consumption.

Technical Informations

Item number	10002941
EAN	4019238130041
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 K
TL/TT	TL
Brand	Continental
Tread pattern	Conti Hybrid HT3+
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	B
Wet grip	C
Rolling noise [db].	70
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	72,00
Recommended rim size	11.75
Maximum air pressure [bar].	9,00
Section width (mm)	381
Tread width (mm)	306
Outer diameter of tyre [mm].	1064
Stat. radius (SLR) [mm]	493
Rolling circumference [mm].	3261
Tread depth (mm)	16,0

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 K	5000	110	Single	9,00	