

RIMS

Product group	Rims
Item number	10002952
Valid rim size	9.00 x 15.3
Rim connection	5/157/205
Bolt hole design	A1
Rim colour	Silver
Brand	Jantsa



Technical Informations

Load capacity of rim 1 [kg]	2900
Speed Rims 1 [km/h]	40
Axle position agriculture 1	Free Rolling
Load capacity of rim 2 [kg]	2450
Speed Rims 2 [km/h]	50
Axle position agriculture 2	Free Rolling
Load capacity of rim 3 [kg]	2050
Speed Rims 3 [km/h]	40
Axle position agriculture 3	Drive Wheel
Load capacity of rim 4 [kg]	1750
Speed of wheels 4 [km/h].	50

Axle position agriculture 4	Drive Wheel
Maximum speed [km/h].	50
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	16,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	8
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	157
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No