

TYRES

| | |
|-----------------|-----------------------|
| Product group | Tyres |
| Item number | 10002970 |
| Valid tyre size | VF 1000 / 50 R 25 CFO |
| LI / SI / PR | 184 D / 181 E |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 377 + |



Notes and features

- The Alliance Agriflex 377+ is a VF tyre for manure spreaders, sprayers, harvesting vehicles and grain carts.
- The new tread ensures a maximum contact area for low soil compaction and optimum traction.
- The rounded tyre shoulder protects the ground and prevents tyre damage caused by stubble.
- VF technology enables up to 40% higher load capacity at the same air pressure compared to standard tyres.
- The steel belted carcass and a strong wear-resistant rubber compound ensure stability and durability.
- The robust rubber compound effectively protects the tyre from damage (Stubble Guard) and ensures a long service life.

Technical Informations

| | |
|--------------------------------------|-----------------------|
| Item number | 10002970 |
| EAN | 7291050085205 |
| Valid tyre size | VF 1000 / 50 R 25 CFO |
| LI / SI / PR | 184 D / 181 E |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 377 + |
| TRA Code | R1 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 351,50 |
| Recommended rim size | 36.0TH / 1.5 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 1030 |
| Outer diameter of tyre [mm]. | 1645 |
| Stat. radius (SLR) [mm] | 703 |
| Speed Radius Index (SRI) | 775 |
| Rolling circumference [mm]. | 4949 |
| Contact area [cm²] | 4651 |
| Tread depth (mm) | 46,0 |
| Number of lugs | 18x2 |
| Tyre capacity 75% [ltr.] | 988.50 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 184 D | 9000 | 65 | | 2,40 | |