

TYRES

Product group	Tyres	
Item number	10002970 VF 1000 / 50 R 25 CFO 184 D / 181 E TL Alliance	
Valid tyre size		
LI / SI / PR		
TL/TT		
Brand		
Tread pattern	Agriflex 377 +	





Notes and features

- The Alliance Agriflex 377+ is a VF tyre for manure spreaders, sprayers, harvesting vehicles and grain carts.
- The new tread ensures a maximum contact area for low soil compaction and optimum traction.
- The rounded tyre shoulder protects the ground and prevents tyre damage caused by stubble.
- VF technology enables up to 40% higher load capacity at the same air pressure compared to standard tyres.
- The steel belted carcass and a strong wear-resistant rubber compound ensure stability and durability.
- The robust rubber compound effectively protects the tyre from damage (Stubble Guard) and ensures a long service life



Technical Informations

Item number	10002970
EAN	7291050085205
Valid tyre size	VF 1000 / 50 R 25 CFO
LI / SI / PR	184 D / 181 E
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 377 +
TRA Code	R1
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	351,50
Recommended rim size	36.0TH / 1.5
Maximum air pressure [bar].	2,40
Section width (mm)	1030
Outer diameter of tyre [mm].	1645
Stat. radius (SLR) [mm]	703
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4949
Contact area [cm²]	4651
Tread depth (mm)	46,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	988.50
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 D	9000	65		2,40	