

## WHEELS

Product group	Wheels
Item number	10002973
Valid wheel size	7.50 - 15 / 6.0
Brand	BKT
Tread pattern	Maglift
Valid rim size	6.0 - 15
Rim connection	6/221/275
Bolt hole design	A2
Offset (mm)	-60
Rim colour	Silver
Load capacity complete wheel [kg]	2800
Speed complete wheel [km/h]	25



## Technical Informations

Assembly Item no. Tyres	• 15770153
Carcass properties	STD Non-Marking Solid Rubber
Antistatic	No
Tyre colour	Grey
Nettogewicht [kg] (gültig)	97,12
ECE regulation number	not necessary
Section width (mm)	193
Side panel width [mm]	193
Tread width (mm)	172
Overall width [mm].	193
Tread depth (mm)	26,0

E-Ready	No
Assembly Item no. Rim	• 10002954
Load capacity of rim 1 [kg]	2800
Speed Rims 1 [km/h]	25
Maximum speed [km/h].	25
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	three-part
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Rim design industry	Standard
Disc thickness [mm]	10
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	16x70

---

Preassembled valve	No
TPMS-kompatibles Ventil	No