

TYRES

Product group	Tyres
Item number	10002996
Valid tyre size	VF 320 / 90 R 54 CFO
LI / SI / PR	168 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

Technical Informations

Item number	10002996
EAN	8903094075249
Valid tyre size	VF 320 / 90 R 54 CFO
LI / SI / PR	168 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	143,04
Recommended rim size	W11
Permitted rim size	W10, DW10, W10L, DW11
Maximum air pressure [bar].	4,40
Section width (mm)	323
Tread width (mm)	275
Outer diameter of tyre [mm].	1948
Stat. radius (SLR) [mm]	910
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5946
Tread depth (mm)	34,5
Number of lugs	40x2
E-Ready	Yes

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		4,40	