

## **TYRES**

Product group	Tyres	
Item number	10002996	
Valid tyre size	VF 320 / 90 R 54 CFO  168 D  TL  BKT	
LI / SI / PR		
TL/TT		
Brand		
Tread pattern	Agrimax Spargo	



## Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.



## **Technical Informations**

Item number	10002000
item number	10002996
EAN	8903094075249
Valid tyre size	VF 320 / 90 R 54 CFO
LI / SI / PR	168 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	143,04
Recommended rim size	W11
Permitted rim size	W10, DW10, W10L, DW11
Maximum air pressure [bar].	4,40
Section width (mm)	323
Tread width (mm)	275
Outer diameter of tyre [mm].	1948
Stat. radius (SLR) [mm]	910
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5946
Tread depth (mm)	34,5
Number of lugs	40x2
E-Ready	Yes

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		4,40	