

WHEELS

Product group	Wheels
Item number	10002997
Valid wheel size	31 X 15.50 - 15
Brand	BKT
Tread pattern	TR 315
Valid rim size	13 LB X 15 H2
Rim connection	6/161/205
Bolt hole design	B2
Rim colour	Silver
Load capacity complete wheel [kg]	1450
Speed complete wheel [km/h]	50



Technical Informations

Assembly Item no. Tyres	• 15710555
LI / SI / PR	121 B, 10 PR
Load capacity 1 [kg]	1450
Speed 1 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	49,69
ECE regulation number	ECE 106
Section width (mm)	390
Stat. radius (SLR) [mm]	354
Rolling circumference [mm].	2320

Tread depth (mm)	20,0
E-Ready	No
Assembly Item no. Rim	• 32010118
Load capacity of rim 1 [kg]	1458
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	2120
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,10
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Number of drain holes	3
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 DS 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade