

## TYRES

Product group	Tyres
Item number	10002998
Valid tyre size	455 / 70 R 24
LI / SI / PR	154 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 525



## Notes and features

- The BKT Multimax MP 525 is an MPT radial tyre for telehandlers, skid steer loaders and graders in agro-industrial use.
- Its all-steel carcass allows high load capacities and higher speeds on and off the road.
- The non-directional tread provides outstanding traction and self-cleaning properties.
- The strong side wall provides exceptional stability when lifting.
- The cut- and puncture-resistant rubber compound protects against damage to ensure a long service life.

## Technical Informations

Item number	10002998
EAN	8903094075195
Valid tyre size	455 / 70 R 24
LI / SI / PR	154 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 525
M+S	M+S
Carcass properties	POR,All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	104,92
Recommended rim size	14
Permitted rim size	13, DW14L
Maximum air pressure [bar].	4,00
Section width (mm)	455
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	571
Rolling circumference [mm].	3794
Tread depth (mm)	23,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 G	3750	90		4,00	