

## WHEELS

Product group	Wheels
Item number	10003003
Valid wheel size	24 x 12.00 - 12
Brand	Kenda
Tread pattern	K472
Valid rim size	8.50 x 12 H2
Rim connection	5/102/139.7
Offset (mm)	-90
Rim colour	Silver
Load capacity complete wheel [kg]	545
Speed complete wheel [km/h]	20



## Technical Informations

Assembly Item no. Tyres	• 19211326
LI / SI / PR	87 A4 / 98 A4, 4 PR
Load capacity 1 [kg]	545
Speed 1 [km/h].	20
Load capacity 2 [kg]	750
Speed 2 [km/h].	20
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	18,27
ECE regulation number	ECE 106
Section width (mm)	302

Rolling circumference [mm].	1810
E-Ready	No
Assembly Item no. Rim	• 30855028
Load capacity of rim 1 [kg]	545
Speed Rims 1 [km/h]	20
Maximum speed [km/h].	20
Maximum air pressure [bar].	1,40
Type of drive	Towed axle
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	15.5
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	102
Bolt hole circle diameter [mm]	139.7
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve

---

Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade