

WHEELS

Product group	Wheels
Item number	10003004
Valid wheel size	6.00 R 9
Brand	BKT
Tread pattern	Liftmax LM 63
Valid rim size	4.00 E - 9
Rim connection	5/94/140
Bolt hole design	A1
Offset (mm)	-5
Rim colour	Silver
Load capacity complete wheel [kg]	1450
Speed complete wheel [km/h]	25



Technical Informations

Assembly Item no. Tyres	• 10002901
LI / SI / PR	121 A5
Load capacity 1 [kg]	1450
Speed 1 [km/h].	25
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	19,35
Section width (mm)	160
E-Ready	No
Assembly Item no. Rim	• 10002967

Load capacity of rim 1 [kg]	1450
Speed Rims 1 [km/h]	25
Maximum speed [km/h].	25
Maximum air pressure [bar].	10,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	geteilt
Quantity multi-piece	two-part
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	5
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Valve seat	External Valve
Valve hole diameter [mm]	13.5
Preassembled valve	No
Valve design	Angled valve

Colour of cap	Black
Valve cap Material	Plastic