Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	10003010
Valid tyre size	460 / 85 R 30
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2



Notes and features

- The Michelin Axiobib 2 is designed for tractors within a performance range of 60 to 170 hp.
- The new optimised tread with a lug angle of 45° offers very good traction transmission to the ground.
- Its particularly high tread depth ensures a long service life for the tyre.
- Thanks to the additional rubber lip along the tread centre, the tyre offers very good self-cleaning properties.
- The angle of the lugs and a rubber reinforcement on the tyre shoulder deflect stubble and protect the tyre from damage.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10003010
EAN	3528708224674
Valid tyre size	460 / 85 R 30
Alternative size 1	18.4R30
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	116,00
Recommended rim size	DW16L
Permitted rim size	W16L, W15, DW15L
Maximum air pressure [bar].	2,40
Section width (mm)	494
Outer diameter of tyre [mm].	1556
Stat. radius (SLR) [mm]	701
Rolling circumference [mm].	4611
Tread depth (mm)	54,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	326
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		2,40	
150 B	3350	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.