

TYRES

Product group	Tyres
Item number	10003011
Valid tyre size	420 / 85 R 28
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2



Notes and features

- The Michelin Axiobib 2 is designed for tractors within a performance range of 60 to 170 hp.
- The new optimised tread with a lug angle of 45° offers very good traction transmission to the ground.
- Its particularly high tread depth ensures a long service life for the tyre.
- Thanks to the additional rubber lip along the tread centre, the tyre offers very good self-cleaning properties.
- The angle of the lugs and a rubber reinforcement on the tyre shoulder deflect stubble and protect the tyre from damage.



Technical Informations

Item number	10003011
EAN	3528701359052
Valid tyre size	420 / 85 R 28
Alternative size 1	16.9R28
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	101,00
Recommended rim size	DW15
Permitted rim size	DW14L, W14L, W15L
Maximum air pressure [bar].	2,40
Section width (mm)	449
Outer diameter of tyre [mm].	1419
Stat. radius (SLR) [mm]	645
Rolling circumference [mm].	4226
Tread depth (mm)	49,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	248
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		2,40	
144 B	2800	50		2,40	