

## **TYRES**

Product group	Tyres
Item number	10003014
Valid tyre size	280 / 85 R 24
LI / SI / PR	120 A8 / 120 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2



## Notes and features

- The Michelin Axiobib 2 is designed for tractors within a performance range of 60 to 170 hp.
- The new optimised tread with a lug angle of 45° offers very good traction transmission to the ground.
- Its particularly high tread depth ensures a long service life for the tyre.
- Thanks to the additional rubber lip along the tread centre, the tyre offers very good self-cleaning properties.
- The angle of the lugs and a rubber reinforcement on the tyre shoulder deflect stubble and protect the tyre from damage.



## **Technical Informations**

Item number	10003014
EAN	3528709904063
Valid tyre size	280 / 85 R 24
Alternative size 1	11.2R24
LI / SI / PR	120 A8 / 120 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	40,00
Recommended rim size	W10
Permitted rim size	W9
Maximum air pressure [bar].	2,40
Section width (mm)	289
Outer diameter of tyre [mm].	1086
Stat. radius (SLR) [mm]	503
Rolling circumference [mm].	3261
Tread depth (mm)	41,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	88
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
120 A8	1400	40		2,40	
120 B	1400	50		2,40	