

WHEELS

Product group	Wheels
Item number	10003015
Valid wheel size	16 x 7.50 - 8
Brand	Kenda
Tread pattern	K500 Super Turf
Valid rim size	5.50 A x 8
Rim connection	4/60/100
Bolt hole design	D12
Rim colour	Silver
Load capacity complete wheel [kg]	265
Speed complete wheel [km/h]	20
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19211191
LI / SI / PR	62 A4 / 73 A4, 6 PR
Load capacity 1 [kg]	265
Speed 1 [km/h].	20
Load capacity 2 [kg]	365
Speed 2 [km/h].	20
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	6,61
ECE regulation number	ECE 106

Section width (mm)	185
Rolling circumference [mm].	1277
E-Ready	No
Assembly Item no. Rim	• 30655030
Load capacity of rim 1 [kg]	575
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	350
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	20
Maximum air pressure [bar].	2,20
Number of bolt holes	4
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	11.3

Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade