# Bohnenkamp Moving Professionals

19.09.2024

### TYRES

Product group	Tyres	
Item number	10003019	
Valid tyre size	600 / 50 - 22.5	
LI / SI / PR	173 A8 / 173 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	399	



#### Notes and features

- The Alliance 839 is a bias tyre for excavators.
- Its non-directional tread pattern with wide blocks in the tread center offers good performance even on soft surfaces.
- It ensures good ride comfort and low wear when driving on the road.
- The open tyre shoulder enables excellent self-cleaning.
- The bias carcass with steel belts (steel belted) guarantees stability and good protection against tyre damage.
- Its high tread depth and low-wear rubber compound ensure a long tyre life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10003019
EAN	8903635053170
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	173 A8 / 173 B
TL/TT	TL
Brand	Alliance
Tread pattern	399
Carcass properties	Steel Belted,C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	121,00
Recommended rim size	AG20.00
Maximum air pressure [bar].	6,00
Section width (mm)	601
Outer diameter of tyre [mm].	1172
Stat. radius (SLR) [mm]	534
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3529
Tread depth (mm)	30,0
Number of lugs	19x2
Guarantee period	5 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



#### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	50		6,00	
173 B	6500	50		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.