

TYRES

Product group	Tyres
Item number	10003021
Valid tyre size	710 / 40 - 22.5
LI / SI / PR	173 A8 / 173 B
TL/TT	TL
Brand	Alliance
Tread pattern	399



Notes and features

- The Alliance 839 is a bias tyre for excavators.
- Its non-directional tread pattern with wide blocks in the tread center offers good performance even on soft surfaces.
- It ensures good ride comfort and low wear when driving on the road.
- The open tyre shoulder enables excellent self-cleaning.
- The bias carcass with steel belts (steel belted) guarantees stability and good protection against tyre damage.
- Its high tread depth and low-wear rubber compound ensure a long tyre life.



Technical Informations

Item number	10003021
EAN	8903635054337
Valid tyre size	710 / 40 - 22.5
LI / SI / PR	173 A8 / 173 B
TL/TT	TL
Brand	Alliance
Tread pattern	399
Carcass properties	Steel Belted,C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	130,80
Recommended rim size	AG24.00
Maximum air pressure [bar].	5,50
Section width (mm)	698
Outer diameter of tyre [mm].	1140
Stat. radius (SLR) [mm]	524
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3493
Tread depth (mm)	30,0
Guarantee period	5 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	40		5,50	
173 B	6500	50		5,50	