

## WHEELS

Product group	Wheels
Item number	10003037
Valid wheel size	26 x 12 - 12
Brand	BKT
Tread pattern	Skid Power HD
Valid rim size	10.50 I x 12 H2
Rim connection	4/60/100
Bolt hole design	A1
Offset (mm)	-70
Rim colour	Silver
Load capacity complete wheel [kg]	800
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15772050
LI / SI / PR	119 A2, 8 PR
Load capacity 1 [kg]	1360
Speed 1 [km/h].	10
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	38,62
ECE regulation number	ECE 106
Section width (mm)	305
Stat. radius (SLR) [mm]	297
Rolling circumference [mm].	1947

Tread depth (mm)	23,5
E-Ready	No
Assembly Item no. Rim	• 30810301
Load capacity of rim 1 [kg]	800
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,40
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve

---

Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade