

## TYRES

|                 |                  |
|-----------------|------------------|
| Product group   | Tyres            |
| Item number     | 10003061         |
| Valid tyre size | VF 480 / 95 R 50 |
| LI / SI / PR    | 181 D            |
| TL/TT           | TL               |
| Brand           | BKT              |
| Tread pattern   | Agrimax Spargo   |



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

**Technical Informations**

|                              |                  |
|------------------------------|------------------|
| Item number                  | 10003061         |
| EAN                          | 8903094075638    |
| Valid tyre size              | VF 480 / 95 R 50 |
| LI / SI / PR                 | 181 D            |
| TL/TT                        | TL               |
| Brand                        | BKT              |
| Tread pattern                | Agrimax Spargo   |
| Antistatic                   | No               |
| Tyre colour                  | Black            |
| ECE regulation number        | ECE 106          |
| Nettogewicht [kg] (gültig)   | 226.13           |
| Recommended rim size         | DW16L            |
| Permitted rim size           | DW15L            |
| Maximum air pressure [bar].  | 3,20             |
| Section width (mm)           | 479              |
| Tread width (mm)             | 410              |
| Outer diameter of tyre [mm]. | 2182             |
| Stat. radius (SLR) [mm]      | 991              |
| Speed Radius Index (SRI)     | 1025             |
| Rolling circumference [mm].  | 6606             |
| Tread depth (mm)             | 43,0             |
| Number of lugs               | 34x2             |
| E-Ready                      | No               |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 181 D | 8250               | 65           |               | 3,20                     |              |