

TYRES

Product group	Tyres
Item number	10003061
Valid tyre size	VF 480 / 95 R 50
LI / SI / PR	181 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

Technical Informations

Item number	10003061
EAN	8903094075638
Valid tyre size	VF 480 / 95 R 50
LI / SI / PR	181 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	226.13
Recommended rim size	DW16L
Permitted rim size	DW15L
Maximum air pressure [bar].	3,20
Section width (mm)	479
Tread width (mm)	410
Outer diameter of tyre [mm].	2182
Stat. radius (SLR) [mm]	991
Speed Radius Index (SRI)	1025
Rolling circumference [mm].	6606
Tread depth (mm)	43,0
Number of lugs	34x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 D	8250	65		3,20	