

## TYRES

Product group	Tyres
Item number	10003062
Valid tyre size	VF 380 / 90 R 54
LI / SI / PR	176 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

## Technical Informations

Item number	10003062
EAN	8903094075614
Valid tyre size	VF 380 / 90 R 54
LI / SI / PR	176 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	185,47
Recommended rim size	W13
Permitted rim size	DW13, DW12, W12
Maximum air pressure [bar].	4,40
Section width (mm)	383
Tread width (mm)	326
Outer diameter of tyre [mm].	2056
Stat. radius (SLR) [mm]	948
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6232
Tread depth (mm)	34,5
Number of lugs	36x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 D	7100	65		4,40	