

TYRES

Product group	Tyres
Item number	10003064
Valid tyre size	710 /45 - 26.5
LI / SI / PR	180 A2 / 173 A8, 24 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 678



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT TR 678 is suitable for use on excavators and loaders, as well as the steel belted version in the agricultural sector.
- In this dimension, the tyre can also be used on forestry machines.
- The tyre is characterised by its good traction and excellent self-cleaning.
- The cut-resistant tread compound reduces the risk of machine failure and increases performance.

Technical Informations

Item number	10003064
EAN	8903094075737
Valid tyre size	710 /45 - 26.5
LI / SI / PR	180 A2 / 173 A8, 24 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 678
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	226,11
Recommended rim size	AG24.00
Maximum air pressure [bar].	6,00
Section width (mm)	705
Outer diameter of tyre [mm].	1345
Tread depth (mm)	48,5
Number of lugs	16x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180 A2	8000	10		6,00	
173 A8	6500	40		6,00	