

RIMS

| | |
|---------------------------------|-----------------|
| Product group | Rims |
| Item number | 10003082 |
| Valid rim size | 6.75 x 17.5 |
| Rim connection | 6/191/245 |
| Offset (mm) | +125 |
| Half centre distance (HMA) [mm] | 146 |
| Brand | Speedline Truck |



Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 2500 |
| Speed Rims 1 [km/h] | 130 |
| Maximum speed [km/h]. | 130 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 14,70 |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | aluminium |
| Surface treatment | Mirror |
| Cavity Sealed | No |
| Disc thickness [mm] | 21 |

| | |
|--------------------------------|----------------|
| Verschweißung beidseitig | No |
| KBA number | KBA 49488 |
| Ventilation holes | Yes |
| Number of bolt holes | 6 |
| Bolt hole diameter [mm] | 30 |
| hub hole diameter [mm]. | 191 |
| Bolt hole circle diameter [mm] | 245 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 9.7 |
| Preassembled valve | Yes |
| Valve design | Metal valve |
| Valve designation ETRTO | V3.22.10 |
| Valve length [mm] | 55.5 |