

## RIMS

|                                 |                 |
|---------------------------------|-----------------|
| Product group                   | Rims            |
| Item number                     | 10003083        |
| Valid rim size                  | 6.75 x 17.5     |
| Rim connection                  | 8/221/275       |
| Offset (mm)                     | +125            |
| Half centre distance (HMA) [mm] | 146             |
| Brand                           | Speedline Truck |



## Technical Informations

|                             |                               |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 2500                          |
| Speed Rims 1 [km/h]         | 130                           |
| Maximum speed [km/h].       | 130                           |
| Type of drive               | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig)  | 14,30                         |
| Hump                        | kein Hump                     |
| Single / multi-part         | einteilig                     |
| Rim material                | aluminium                     |
| Surface treatment           | Diamond                       |
| Cavity Sealed               | No                            |
| Disc thickness [mm]         | 21                            |

---

|                                |                |
|--------------------------------|----------------|
| Verschweißung beidseitig       | No             |
| KBA number                     | KBA 49855      |
| Ventilation holes              | Yes            |
| Number of bolt holes           | 8              |
| Bolt hole diameter [mm]        | 24             |
| hub hole diameter [mm].        | 221            |
| Bolt hole circle diameter [mm] | 275            |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 9.7            |
| Preassembled valve             | Yes            |
| Valve design                   | Metal valve    |
| Valve designation ETRTO        | V3.22.10       |
| Valve length [mm]              | 55.5           |