

## RIMS

|                |                 |
|----------------|-----------------|
| Product group  | Rims            |
| Item number    | 10003095        |
| Valid rim size | 11.75 x 22.5    |
| Rim connection | 10/281/335      |
| Offset (mm)    | +135            |
| Brand          | Speedline Truck |



## Technical Informations

|                             |                               |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 5000                          |
| Speed Rims 1 [km/h]         | 120                           |
| Maximum speed [km/h].       | 120                           |
| Type of drive               | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig)  | 25,90                         |
| Hump                        | kein Hump                     |
| Single / multi-part         | einteilig                     |
| Rim material                | aluminium                     |
| Surface treatment           | Mirror                        |
| Cavity Sealed               | No                            |
| Disc thickness [mm]         | 25                            |

---

|                                |                |
|--------------------------------|----------------|
| Verschweißung beidseitig       | No             |
| KBA number                     | KBA 48899      |
| Ventilation holes              | Yes            |
| Number of bolt holes           | 10             |
| Bolt hole diameter [mm]        | 26             |
| hub hole diameter [mm].        | 281            |
| Bolt hole circle diameter [mm] | 335            |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 9.7            |
| Preassembled valve             | Yes            |
| Valve design                   | Metal valve    |
| Valve designation ETRTO        | V3.22.9        |
| Valve length [mm]              | 36.0           |