

RIMS

Product group	Rims
Item number	10003097
Valid rim size	8.25 x 22.5
Rim connection	10/281/335
Offset (mm)	+146
Half centre distance (HMA) [mm]	166.5
Brand	Speedline Truck



Technical Informations

Load capacity of rim 1 [kg]	3750
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	23,20
Hump	kein Hump
Single / multi-part	einteilig
Rim material	aluminium
Surface treatment	Diamond
Cavity Sealed	No
Disc thickness [mm]	20.5

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
KBA number	KBA 48829
Ventilation holes	Yes
Number of bolt holes	10
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
Valve design	Metal valve
Valve designation ETRTO	V3.22.10
Valve length [mm]	55.5