

WHEELS

| | |
|-----------------------------------|-----------------|
| Product group | Wheels |
| Item number | 10003115 |
| Valid wheel size | 23 x 10.50 - 12 |
| Brand | BKT |
| Tread pattern | TR 315 |
| Valid rim size | 8.50 x 12 H2 |
| Rim connection | 5/102/139.7 |
| Offset (mm) | -60 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 710 |
| Speed complete wheel [km/h] | 30 |



Technical Informations

| | |
|-----------------------------|-------------|
| Assembly Item no. Tyres | • 15710495 |
| LI / SI / PR | 96 A6, 6 PR |
| Load capacity 1 [kg] | 710 |
| Speed 1 [km/h]. | 30 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 18,66 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 255 |
| Stat. radius (SLR) [mm] | 272 |
| Rolling circumference [mm]. | 1840 |

| | |
|--------------------------------|----------------|
| Tread depth (mm) | 15,5 |
| Number of lugs | 15x2 |
| E-Ready | No |
| Assembly Item no. Rim | • 30855024 |
| Load capacity of rim 1 [kg] | 800 |
| Speed Rims 1 [km/h] | 15 |
| Load capacity of rim 2 [kg] | 710 |
| Speed Rims 2 [km/h] | 30 |
| Maximum speed [km/h]. | 30 |
| Maximum air pressure [bar]. | 2,20 |
| Hump | H2 |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole diameter [mm] | 15.5 |
| hub hole diameter [mm]. | 102 |
| Bolt hole circle diameter [mm] | 139.7 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 11.3 |
| Preassembled valve | No |
| Valve design | Rubber valve |

| | |
|-------------------------|---------|
| Valve designation ETRTO | V2.03.1 |
| Valve length [mm] | 43.0 |
| Valve angle [°] | gerade |