

RIMS

Product group	Rims
Item number	10003123
Valid rim size	14.00 x 22.5
Rim connection	10/335/281
Bolt hole design	M22
Rim colour	Silver
Brand	Jantsa



Technical Informations	
Load capacity of rim 1 [kg]	6000
Speed Rims 1 [km/h]	100
Load capacity of rim 2 [kg]	5900
Speed Rims 2 [km/h]	110
Maximum speed [km/h].	110
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	54,21
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Disc thickness [mm]	15
Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	НВ
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	335
Bolt hole circle diameter [mm]	281
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No