

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 10003133 |
| Valid tyre size | 500 / 50 - 22.5 |
| LI / SI / PR | 151 A8 / 163 A8, 20 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 328 Value Plus |



Notes and features

- Flotation tyre with traction pattern for light conditions, e.g. on towed and mounted equipment as well as agricultural trailers, presses etc.
- Very good self-cleaning properties and simultaneous soil protection due to traction tread pattern.
- Rounded shoulders additionally protect green areas and plant stock.
- Not suitable for heavy vehicles and/or long road journeys under high loads.

Technical Informations

| | |
|---------------------------------|------------------------|
| Item number | 10003133 |
| EAN | 8903635065586 |
| Valid tyre size | 500 / 50 - 22.5 |
| LI / SI / PR | 151 A8 / 163 A8, 20 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 328 Value Plus |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 62,50 |
| Recommended rim size | AG16.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 503 |
| Outer diameter of tyre [mm]. | 1085 |
| Stat. radius (SLR) [mm] | 488 |
| Speed Radius Index (SRI) | 525 |
| Rolling circumference [mm]. | 3291 |
| Contact area [cm ²] | 1402.2 |
| Tread depth (mm) | 22,0 |
| Number of lugs | 26x2 |
| Tyre capacity 75% [ltr.] | 168.30 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 151 A8 | 3450 | 40 | Drive Wheel | 4,00 | |
| 163 A8 | 4875 | 40 | Free Rolling | 4,00 | |