

## TYRES

Product group	Tyres
Item number	10003224
Valid tyre size	26.5 R 25
LI / SI / PR	210 A8
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 41



## Notes and features

- The improved tread design provides maximum traction.
- All steel carcass with reinforced steel belt ply provides excellent stability and puncture resistance.
- The special tread compound (C.R. = Cut Resistance) offers best cut resistance in combination with excellent mileage and wear properties.
- Especially suitable for use on wheel loaders and dumpers.
- Important: Mounting only permitted on multi-part rim.

## Technical Informations

Item number	10003224
EAN	8903094056583
Valid tyre size	26.5 R 25
LI / SI / PR	210 A8
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 41
TRA Code	E4
Star Rating	****
Carcass properties	C.R.,UMS
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	555,00
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	8,00
Section width (mm)	678
Outer diameter of tyre [mm].	1742
Stat. radius (SLR) [mm]	775
Rolling circumference [mm].	5150
Tread depth (mm)	59,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
210 A8	19000	40	Loader dozer	8,00	