Bohnenkamp
Moving Professionals

TYRES

Product group	Tyres
Item number	10003225
Valid tyre size	28 x 12.5 - 15 / 9.75
LI / SI / PR	159 A5
Brand	Maxam
Tread pattern	MS700

Notes and features

- The Maxam MS700 is a solid rubber tyre for use on forklift trucks.

- Its extra-wide tread enables excellent lifting capacity.

- The tread pattern ensures traction, comfortable handling, good maneuverability and even wear.

- The construction typical of premium tyres with a high-quality 3-layer rubber compound (tread, spring and base compound) ensures smooth running and driving comfort.

- Thanks to the EcoPoint3 rubber compound, the tyre is particularly wear-resistant and protected against damage.

Technical Informations

Item number	10003225
EAN	8936096307308
Valid tyre size	28 x 12.5 - 15 / 9.75
Alternative size 1	355/45-15
LI / SI / PR	159 A5
Brand	Maxam
Tread pattern	MS700
Carcass properties	STD,Solid Rubber
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	87,52
Recommended rim size	9.75
Section width (mm)	285
Outer diameter of tyre [mm].	711
Stat. radius (SLR) [mm]	356
Rolling circumference [mm].	2234
Tread depth (mm)	55,9
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A5	4375	25	Steering wheel		
	5688	25	Load wheel		