

## RIMS

Product group	Rims
Item number	10003248
Valid rim size	7.5 - 20
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	+35
Rim colour	Silver
Brand	Jamak

## Technical Informations

Load capacity of rim 1 [kg]	4000
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	5200
Speed Rims 2 [km/h]	25
Maximum speed [km/h].	25
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	54,00
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	one-part
Rim material	steel

---

<b>RAL</b>	RAL9006
<b>Cavity Sealed</b>	No
<b>Rim design industry</b>	Lip
<b>Disc thickness [mm]</b>	13
<b>Knurling</b>	without knurling
<b>Verschweißung beidseitig</b>	No
<b>Ventilation holes</b>	No
<b>Rim centering</b>	BC
<b>Number of bolt holes</b>	6
<b>Bolt hole design EUWA</b>	B18 ES 32
<b>Bolt hole diameter [mm]</b>	21.5
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R16
<b>hub hole diameter [mm].</b>	161
<b>Bolt hole circle diameter [mm]</b>	205
<b>Preassembled valve</b>	No