

TYRES

Product group	Tyres	
Item number	10003283	
Valid tyre size	6.50 - 10 / 5.00 F	
LI / SI / PR	128 A5	
Brand	Maxam	
Tread pattern	MS701+	





Notes and features

- The Maxam MS701+ Industrial Pro is a solid rubber tyre for forklifts and wheeled excavators.
- The construction, typical of premium tyres, with a highquality 3-layer rubber compound (tread, spring and base compound) ensures smooth running and driving comfort in use.
- The particularly abrasion and cut resistant rubber compound ensures a very high wear resistance.
- Its large tread depth allows maximum traction.
- Due to the large contact area, the load is evenly distributed and good stability is achieved.
- The MS701+ is currently available in the Standard version.



Technical Informations

Item number	10003283
EAN	6959655468649
Valid tyre size	6.50 - 10 / 5.00 F
LI / SI / PR	128 A5
Brand	Maxam
Tread pattern	MS701+
Carcass properties	STD,Solid Rubber
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	33,08
Recommended rim size	5.00F
Section width (mm)	162
Outer diameter of tyre [mm].	574
Stat. radius (SLR) [mm]	287
Rolling circumference [mm].	1803
Tread depth (mm)	51,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 A5	1800	25	Steering wheel		
	2340	25	Load wheel		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.