

TYRES

Product group	Tyres
Item number	10003302
Valid tyre size	VF 380 / 105 R 54
LI / SI / PR	180 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

Technical Informations

Item number	10003302
EAN	8903094075843
Valid tyre size	VF 380 / 105 R 54
LI / SI / PR	180 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	218,57
Recommended rim size	W13A
Permitted rim size	W12, DW12, DW13, DW13L
Maximum air pressure [bar].	4,40
Section width (mm)	400
Tread width (mm)	345
Outer diameter of tyre [mm].	2140
Stat. radius (SLR) [mm]	984
Speed Radius Index (SRI)	1050
Rolling circumference [mm].	6503
Tread depth (mm)	37,0
Number of lugs	38x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180 D	8000	65		4,40	