

WHEELS

| | |
|-----------------------------------|----------------|
| Product group | Wheels |
| Item number | 10003317 |
| Valid wheel size | 27 x 10.5 - 15 |
| Brand | BKT |
| Tread pattern | Skid Power HD |
| Valid rim size | W 8 x 15 |
| Rim connection | 6/161/205 |
| Bolt hole design | B2 |
| Offset (mm) | +60 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 925 |
| Speed complete wheel [km/h] | 40 |



Technical Informations

| | |
|----------------------------|--------------|
| Assembly Item no. Tyres | • 15772091 |
| LI / SI / PR | 105 A8, 8 PR |
| Load capacity 1 [kg] | 925 |
| Speed 1 [km/h]. | 40 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 32,68 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 256 |
| Stat. radius (SLR) [mm] | 326 |
| Speed Radius Index (SRI) | 550 |

| | |
|-----------------------------|-------------------------------|
| Rolling circumference [mm]. | 2037 |
| Tread depth (mm) | 14,5 |
| E-Ready | No |
| Assembly Item no. Rim | • 10001530 |
| Load capacity of rim 1 [kg] | 1800 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 1620 |
| Speed Rims 2 [km/h] | 40 |
| Maximum speed [km/h]. | 40 |
| Maximum air pressure [bar]. | 4,20 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | kein Hump |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Disc thickness [mm] | 7 |
| Knurling | without knurling |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 6 |
| Bolt hole design EUWA | B18 DS 32 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |

| | |
|--------------------------------|----------------|
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| Valve design | Rubber valve |
| Valve designation ETRTO | V2.03.3 |
| Valve length [mm] | 43.0 |
| Valve angle [°] | gerade |