

TYRES

Product group	Tyres
Item number	10003324
Valid tyre size	VF 750 / 60 R 46
LI / SI / PR	189 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

Technical Informations

Item number	10003324
EAN	8903094075652
Valid tyre size	VF 750 / 60 R 46
LI / SI / PR	189 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	352,92
Recommended rim size	DW27B
Permitted rim size	DW25B
Maximum air pressure [bar].	3,20
Section width (mm)	755
Tread width (mm)	665
Outer diameter of tyre [mm].	2086
Stat. radius (SLR) [mm]	940
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6337
Tread depth (mm)	38,0
Number of lugs	26x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
189 D	10300	65		3,20	