

TYRES

Product group	Tyres
Item number	10003336
Valid tyre size	340 / 80 - 18
LI / SI / PR	143 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star



Notes and features

- A sturdy tyre with reinforced sidewall for good stability in lifting mode.
- Wide studs with large contact area to carry heavy loads.
- Resistant rubber compound for best cut & puncture resistance for longer service life.
- Especially suitable for telescopic, wheeled & backhoe loaders.

Technical Informations

Item number	10003336
EAN	8903094051304
Valid tyre size	340 / 80 - 18
Alternative size 1	12.5/80-18
LI / SI / PR	143 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	52,06
Recommended rim size	11
Permitted rim size	W10, 11SDC, W11, 12, 12SDC
Maximum air pressure [bar].	4,00
Section width (mm)	350
Outer diameter of tyre [mm].	1015
Stat. radius (SLR) [mm]	465
Rolling circumference [mm].	3040
Tread depth (mm)	30,5
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	40	Loader dozer	4,00	