

TYRES

Product group	Tyres
Item number	10003338
Valid tyre size	460 / 70 - 24
LI / SI / PR	159 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star



Notes and features

- A sturdy tyre with reinforced sidewall for good stability in lifting mode.
- Wide studs with large contact area to carry heavy loads.
- Resistant rubber compound for best cut & puncture resistance for longer service life.
- Especially suitable for telescopic, wheeled & backhoe loaders.

Technical Informations

Item number	10003338
EAN	8903094052424
Valid tyre size	460 / 70 - 24
Alternative size 1	17.5L-24
LI / SI / PR	159 A8
TL/TT	TL
Brand	BKT
Tread pattern	Con Star
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	93,94
Recommended rim size	DW15L
Permitted rim size	DW14L, DW16L
Maximum air pressure [bar].	4,00
Section width (mm)	460
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	562
Rolling circumference [mm].	3784
Tread depth (mm)	33,5
Number of lugs	16x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40	Loader dozer	4,00	