

TYRES

Product group	Tyres
Item number	10003347
Valid tyre size	AT 25 x 8 - 12
LI / SI / PR	43 N, 6 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K3215



Notes and features

- The Kenda K3215 is a cross-ply ATV tyre for hard to medium-hard surfaces.
- Its directional tread pattern with wide blocks in the centre of the tread ensures a smooth ride on the road.
- The distinctive shoulder lugs guarantee very good lateral stability and traction on any terrain.



Technical Informations

Item number	10003347
EAN	4711041542409
Valid tyre size	AT 25 x 8 - 12
Alternative size 1	205/80-12
LI / SI / PR	43 N, 6 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K3215
Star Rating	***
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	9,20
Recommended rim size	6.0
Permitted rim size	6.5
Maximum air pressure [bar].	0,50
Section width (mm)	198
Outer diameter of tyre [mm].	618
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
43 N	155	140		0,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.