

TYRES

Product group	Tyres
Item number	10003348
Valid tyre size	AT 25 x 10 - 12
LI / SI / PR	50 N, 6 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K3215



Notes and features

- The Kenda K3215 is a cross-ply ATV tyre for hard to medium-hard surfaces.
- Its directional tread pattern with wide blocks in the centre of the tread ensures a smooth ride on the road.
- The distinctive shoulder lugs guarantee very good lateral stability and traction on any terrain.

Technical Informations

Item number	10003348
EAN	4711041542416
Valid tyre size	AT 25 x 10 - 12
Alternative size 1	255/65-12
LI / SI / PR	50 N, 6 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K3215
Star Rating	***
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	10,32
Recommended rim size	7.5
Permitted rim size	6.5, 7.0, 8.0
Maximum air pressure [bar].	0,50
Section width (mm)	238
Outer diameter of tyre [mm].	637
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
50 N	190	140		0,50	