

TYRES

Product group	Tyres
Item number	10003350
Valid tyre size	650 / 65 R 38
LI / SI / PR	164 A8 / 160 B
TL/TT	TL
Brand	ВКТ
Tread pattern	Forestmax



Technical Informations

Item number	10003350
EAN	8903094074044
Valid tyre size	650 / 65 R 38
LI / SI / PR	164 A8 / 160 B
TL/TT	TL
Brand	BKT
Tread pattern	Forestmax
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	269,00

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Recommended rim size	DW20B
Permitted rim size	DW21B, DW23B
Maximum air pressure [bar].	2,40
Section width (mm)	645
Outer diameter of tyre [mm].	1811
Stat. radius (SLR) [mm]	832
Rolling circumference [mm].	5467
Tread depth (mm)	51,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		2,40	
160 B	4500	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.