

## WHEELS

Product group	Wheels
Item number	10003367
Valid wheel size	245 / 70 R 17.5
Brand	Sailun
Tread pattern	SAR1
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	M22
Offset (mm)	+55
Rim colour	Silver
Load capacity complete wheel [kg]	2725
Speed complete wheel [km/h]	100



 **SAILUN**  
TYRE

## Technical Informations

Assembly Item no. Tyres	• 11066136
LI / SI / PR	143 / 141 J (146 / 146 F), 18 PR
Load capacity 1 [kg]	2725
Speed 1 [km/h].	100
Load capacity 2 [kg]	3000
Speed 2 [km/h].	80
Load capacity 3 [kg]	2575
Speed 3 [km/h].	100
Load capacity 4 [kg]	3000
Speed 4 [km/h].	80
M+S	M+S

3PMSF	3PMSF
Axle position truck	FA TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	57,71
ECE regulation number	ECE 54 ECE 117 Vecto Certificate
Section width (mm)	245
Stat. radius (SLR) [mm]	364.36
Rolling circumference [mm].	2299
Tread depth (mm)	13,0
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 10002141
Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	65
Load capacity of rim 2 [kg]	3000
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	8,75
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

---

Cavity Sealed	No
Disc thickness [mm]	12
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade