

TYRES

Product group	Tyres
Item number	10003387
Valid tyre size	500 / 45 R 22.5
LI / SI / PR	136 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 635



Notes and features

- Modern flotation tyre with traction block tread
- Robust heavy-duty nylon casing with strengthened polyester belt plies
- Particularly suitable for balers (especially for green fodder recovery) and other towed agricultural machines
- Open block tread pattern and rounded shoulders ensure optimal grassland protection
- Traction tread pattern ensures good grip in wet conditions as well as fast self-cleaning

Technical Informations

Item number	10003387
EAN	8903094075607
Valid tyre size	500 / 45 R 22.5
LI / SI / PR	136 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 635
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	69,30
Recommended rim size	AG16.00
Maximum air pressure [bar].	2,80
Section width (mm)	490
Outer diameter of tyre [mm].	1022
Stat. radius (SLR) [mm]	461
Rolling circumference [mm].	3086
Tread depth (mm)	21,6
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 D	2240	65		2,80	
	3050	40			
	3540	25			