

TYRES

Product group	Tyres	
Item number	10003421	
Valid tyre size	VF 300 / 95 R 52	
LI / SI / PR	160 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 363 + XT	



Technical Informations

Item number	10003421
EAN	8903635056256
Valid tyre size	VF 300 / 95 R 52
LI / SI / PR	160 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 363 + XT
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Nettogewicht [kg] (gültig)	116,50
Recommended rim size	W10
Permitted rim size	W9
Maximum air pressure [bar].	4,40
Section width (mm)	300
Outer diameter of tyre [mm].	1891
Stat. radius (SLR) [mm]	886.3
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5758
Contact area [cm²]	1231.09
Tread depth (mm)	37,0
Number of lugs	39x2
Tyre capacity 75% [ltr.]	205.20
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 D	4500	65		4,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.